

WHAT IS CLAIMED IS:

1. A storage device comprising:
a field emitter for generating an electron beam current;
a storage medium in close proximity to the field emitter, the storage
5 medium having a plurality of storage areas for storage of information, each of
the plurality of storage areas being in one of a plurality of states to represent the
information stored in that storage area;
such that:
an effect is generated when the electron beam current bombards
10 one of the storage areas;
the magnitude of the effect depends on the state of the bombarded
storage area; and
the information stored in the bombarded storage area is read by
measuring the magnitude of the effect; and
15 an electron beam steering mechanism for deflecting the electron beam
current to different ones of the storage areas.
2. The storage device of claim 1, wherein the electron beam steering
mechanism comprises:
20 a first set of electrodes for deflecting the electron beam current in a first
direction; and
a second set of electrodes for deflecting the electron beam current in a
second direction substantially perpendicular to the first direction.
- 25 3. The storage device of claim 1, and further comprising:
a micromover for causing a change in the relative positions between the
field emitter and the storage medium.

4. The storage device of claim 3, wherein the micromover is configured to cause movement of the field emitter.
5. The storage device of claim 3, wherein the micromover is configured to cause movement of the storage medium.
6. The storage device of either claim 1 or 3, wherein the electron beam current traces out a periodic trajectory on the storage medium.
7. The storage device of claim 6, wherein the shape of the periodic trajectory is one of a circle, ellipse, spiral, square, rectangle and figure 8.
8. The storage device of claim 6, wherein the shape of the periodic trajectory is one of a triangle wave shape, a sawtooth wave shape, a Lissajous wave shape, a rectangle wave shape, and a sinusoidal wave shape.
9. The storage device of claim 1, wherein at least a portion of the information stored in the storage areas is stored and read based on pulse width modulation (PWM).
10. The storage device of claim 1, and further comprising:
a plurality of field emitters, each being similar to the field emitter recited in claim 1, such that the plurality of field emitters work in parallel to read information from the device; and
a plurality of electron beam steering mechanisms for deflecting the electron beam currents from the plurality of field emitters to different ones of the storage areas.
11. A method of accessing information from a storage medium, the storage medium including a plurality of storage areas for storing information, each

storage area being in one of a plurality of states to represent the information stored in that storage area, the method comprising:

- generating an electron beam current with a field emitter, the electron beam current directed toward a first one of the storage areas on the storage medium;
- detecting an effect in the first one of the storage areas caused by the electron beam current, the effect based on the state of the storage area; and steering the electron beam current to multiple ones of the storage areas.

12. The method of claim 11, wherein steering the electron beam current comprises:
- deflecting the electron beam current in a first direction with a first deflection mechanism; and
- deflecting the electron beam current in a second direction substantially perpendicular to the first direction with a second deflection mechanism.
13. The method of claim 11, and further comprising:
- generating a change in the relative positions between the field emitter and the storage medium.
14. The method of claim 13, wherein the generating a change step includes moving the field emitter.
15. The method of claim 13, wherein the generating a change step includes moving the storage medium.
16. The method of either claim 11 or 13, wherein the electron beam current traces out a periodic trajectory on the storage medium.

